

[previous](#) [up](#) [next](#)

Tartalomjegyzék

- 1 Exercises
 - ◆ 1.1
 - Dynamic programming
 - ◊ 1.1.1
Euclidean algorithm
 - ◊ 1.1.2
Paint Bucket Tool
 - ◊ 1.1.3
Knight
 - ◆ 1.2
 - Finite-state machine
 - ◊ 1.2.1
Keystrokes
 - ◊ 1.2.2
Parenthesis

Exercises

Dynamic programming

Euclidean algorithm

Implement the greatest common divisor (gcd) function using the [Euclidean algorithm](#). Implement it with and without recursion!

Paint Bucket Tool

Download the picture.txt file and read it as a list of lists in python!

```
....#####.....  
.....  
.....  
.....  
.....
```

Write a function **fill(x,y)** which fills a territory starting with the given coordinates, like the bucket tool in Paint.

Starting from the (x, y) coordinate replace `.` with `#`, if you encounter a `#` then stop. Do this recursively for every neighbor of the given point. This will fill out an enclosed territory.

Knight

Let's say that you have a knight on the chessboard. Calculate how many steps does it take to optimally reach the other places on the board.

Write a function **knight(x,y)** where the parameters are the x, y coordinates of the initial place. Return an 8-by-8 table of integers containing the minimum number of steps to reach that position. For example the initial state should have 0 on it.

Use a dynamic programming table!

Finite-state machine

Keystrokes

Download the following text file: [raw_data.txt](#)

This file contains keystroke data when someone was typing. The interesting part starts from the 5th line:

- The first column is an event: **keydown** or **keyup** (others are irrelevant now)
- The next three numbers encode the key, actually the second one is important (third column).
- The fourth column refers to capital or lowercase, but that's also irrelevant now.
- The last one is a timestamp, the number of milliseconds elapsed since January 1st, 1970.

The exercise is to process the keystrokes and reconstruct the typed text. Mind that there is a SHIFT key in the data.

Hint:

- Store a dictionary of keys which are pressed at a given time.
- If a key is released, and it was in the dictionary, then that letter was entered.
 - ◆ In this case, erase that key from the dictionary.
- Store the state of the SHIFT key (up or down)
- There is also a BACKSPACE key!
- You can see the [keycodes here](#)

Parenthesis

Given a string, replace the enclosed parts of the string with a \$ character. A formula is enclosed if it is surrounded by parenthesis. For example:

(xc) aa (c (b)) → \$\$\$\$\$aa\$\$\$\$\$\$\$

Note that the parenthesis can be enclosed into each other.

[previous](#) [up](#) [next](#)