

[previous](#) [up](#) [next](#)

Tartalomjegyzék

- [1 Exercises](#)
 - ◆ [1.1 Dynamic programming](#)
 - ◇ [1.1.1 Greatest common divisor](#)
 - ◇ [1.1.2 Pascal triangle](#)
 - ◇ [1.1.3 Paint Bucket Tool](#)
 - ◇ [1.1.4 Knight](#)
 - ◆ [1.2 Finite-state machine](#)
 - ◇ [1.2.1 Parenthesis](#)
 - ◇ [1.2.2 Keystrokes](#)

Exercises

Dynamic programming

Greatest common divisor

Implement the Euclidean algorithm with recursion and without recursion!

Pascal triangle

Write a function that returns the n^{th} row of the Pascal triangle as a list.

Paint Bucket Tool

Save the following "http://wiki.math.bme.hutext"http://wiki.math.bme.hu as a list of lists in python!

```
.....
...#####.....
...#.....#.....
...#.....#.....
...#.....#.....
...#.....#.....
...#.....#.....
...#.....#####.....
...###.....##.....#.....
...#..##.....##.....#.....
...#...##.....##.....#.....
```

```

...#.....##.....##.....#.....
...#.....#####.....#.....
...#.....#.....#.....#.....
...#.....##.....#.....#.....
...#.....##.....#.....#.....
...#.....##.....#.....#.....
...#####.....
.....
.....
.....
.....

```

Write a function **fill(x,y)** which fills a territory starting with the given coordinates, like the bucket tool in Paint.

Starting from the (x, y) coordinate replace . with #, if you encounter a # then stop. Do this recursively for every neighbor of the given point. This will fill out an enclosed territory.

Knight

Let's say that you have a knight on the chessboard. Calculate how many steps does it take to optimally reach the other places on the board.

Write a function **knight(x,y)** where the parameters are the x, y coordinates of the initial place. Return an 8-by-8 table of integers containing the minimum number of steps to reach that position. For example the initial state should have 0 on it.

Use a dynamic programming table!

Finite-state machine

Parenthesis

Given a string, replace the enclosed parts of the string with a \$ character. A formula is enclosed if it is surrounded by parenthesis. For example:

```
(xc) aa (c (b) ) -> $$$$aa$$$$$$
```

Note that the parenthesis can be enclosed into each other.

Keystrokes

Download the following text file: [raw_data.txt](#)

This file contains keystroke data when someone was typing. The interesting part starts from the 5th line:

- The first column is an event: **keydown** or **keyup** (others are irrelevant now)
- The next three numbers encode the key, actually the second one is important (third column).
- The fourth column refers to capital or lowercase, but that's also irrelevant now.
- The last one is a timestamp, the number of milliseconds elapsed since January 1st, 1970.

The exercise is to process the keystrokes and reconstruct the typed text. Mind that there is a SHIFT key in the data.

Hint:

- Store a dictionary of keys which are pressed at a given time.
- if a key is released, and it was in the dictionary, then that letter was entered.
 - ♦ in this case, erase that key from the dictionary.
- store the state of the SHIFT key (up or down)
- There is also a BACKSPACE key!
- You can see the [keycodes here](#)

[previous](#) [up](#) [next](#)